

# ATS Redundant PDU: ATS-3611-M

## Features

<b>Installed in Rack</b>	Horizontally
<b>Power Monitor</b>	Web
<b>Power Control</b>	Web
<b>Power Action</b>	Automatic Transfer Switch
<b>Event Alert</b>	Email, Trap
<b>Protection</b>	Circuit Breaker
<b>Includes</b>	Mounting Bracket

## Specification

<b>Communication</b>	
LAN Interface	1 x RJ45 ; 10/100M Auto Detect
<b>Input</b>	
Nominal Voltage	110 to 130 VAC
On-Line Voltage	100 to 143 VAC
Frequency	50/60 HZ
Connector	2 x NEMA L5-30P Power Cord 12 inches
Protection	2 x Circuit Breaker 30A
Surge	500 Joules
<b>Output</b>	
Connector	12 x IEC 320-C13 (4 segments)
Protection	4 x Circuit Breaker 10A
Power	2400 VA
Max. Current	24A
Detection and transfer time	50Hz < 20 ms; 60Hz < 16ms
	50Hz < 10 ms; 60Hz < 8ms
<b>Operation</b>	
Operation Temp.	0 - 40 degree C
Storage Temp.	-30 - 60 degree C
Relative Humidity	10% to 80%; non-condensing
Operation Altitude	0 to 3,000 M (10,000 ft)
Size L x W x H	44 x 432 x 216 mm
Weight	7 kg