

Monitored PDU: AMz-3223-24-3

Features

| | |
|-----------------------------|---------------------------------|
| Current Meter | Digital True RMS Current Meter |
| Installed in Rack | Vertical |
| Remote Power Monitor | Web, SNMP, Free Bundle Software |
| Audible Alarm | 2 Phase, Warning and Overload |
| Event Alert | Email, Trap, Audible Alarm |
| Protection | Circuit Breaker |
| Includes | Mounting Bracket |

Specification

| | |
|------------------------|---|
| General | |
| Output | (21) IEC 320 C13 (3) IEC 320 C19 |
| Input | (1) IEC 320 309 attached power cord, 3 meters long |
| Protection | (3) 16 AMP Circuit Breaker |
| Communication | |
| IP Address | (1) Yellow LED |
| PDU Status | (1) Green LED |
| Power Monitor | (1) RJ45 for Ethernet |
| Temp./Humidity Monitor | (1) RJ11 |
| Current | 3 Digits Meter Range: 0A ~ 20A Resolution: 0.1A Precision: $\pm 2\% \pm 0.1\text{AMP}$ |
| Operation | |
| Input Voltage | 230V |
| Output Range | 160-320V |
| Frequency | 50/60HZ full range |
| Max. Output Current | 32 Amp |
| Temperature | 0 ~ 40 Celsius degree |
| Humidity | 0% ~ 90% |
| Size | 38 x 1024 x 44 mm |

Weight

4 kg