

Remote Power Manager: RPM-1522/2-MNP

Features

Installed in Rack	Horizontal
Power Monitor	Meter, Web, SNMP, Free Bundle Software
Power Control	Web, SNMP, API, Telephone, Manual
Power Action	Power on Sequential. Safe shutdown. Safe Reboot
Daisy Chain	Up to 15 units.
Event Alert	Email, Trap
Co-operate Device	Temp./Humidity Probe, UPS.
Protection	Circuit Breaker
OS Safe Shutdown	Windows, Linux
Includes	Mounting Bracket

Specification

SNMP Card	
LAN Interface	1 x RJ45 ; 10/100M Auto Detect
Modem	1 x RS232
ENV	1 x RJ11
Reset Key	1 x Button
Hardware	
iLink Interface	2 x RJ11, Connect to UPS, RPM up to 15 RPM client
Phone Interface	2 x RJ11
NT Safe Shutdown	2 x RJ11
Power Control	1 x Master
Output	2 x IEC320R
Input	1 x Input Connector IEC320P
Power Protection	7 Amp Circuit Breaker
Operation	
Nominal Input Voltage	220V
Input Voltage Range	160-320V
Frequency	50/60HZ full range
Maximum Output Capacity	7Amp
Operating Temperature	0 TO 40 degree C
Relative Humidity	0 - 95% non-condensing
Size L x W x H	88 x 180 x 185 mm 1.8 kg UL, FCC