

# Remote Power Manager: RPM-1511/2-MNP

## Features

<b>Installed in Rack</b>	Horizontal
<b>Power Monitor</b>	Meter, Web, SNMP, Free Bundle Software
<b>Power Control</b>	Web, SNMP, API, Telephone, Manual
<b>Power Action</b>	Power on Sequential. Safe shutdown. Safe Reboot
<b>Daisy Chain</b>	Up to 15 units.
<b>Event Alert</b>	Email, Trap
<b>Co-operate Device</b>	Temp./Humidity Probe, UPS.
<b>Protection</b>	Circuit Breaker
<b>OS Safe Shutdown</b>	Windows, Linux
<b>Includes</b>	Mounting Bracket

## Specification

<b>SNMP Card</b>	
LAN Interface	1 x RJ45 ; 10/100M Auto Detect
Modem	1 x RS232
ENV	1 x RJ11
Reset Key	1 x Button
<b>Hardware</b>	
iLink Interface	2 x RJ11, Connect to UPS, RPM up to 15 RPM client
Phone Interface	2x RJ11
NT Safe Shutdown	2 x RJ11
Power Control	1 x Master
Output	2 x NEMA 5-15R
Input	1 x NEMA 5-15P
Power Protection	15 Amp Circuit Breaker
<b>Operation</b>	
Nominal Input Voltage	110V
Input Voltage Range	85-165V
Frequency	50/60HZ full range
Maximum Output Capacity	15Amp
Operating Temperature	0 TO 40 degree C
Relative Humidity	0 - 95% non-condensing
Size L x W x H	88 x 180 x 185 mm 1.8 kg UL, FCC