

# Switched PDU: AMz-3020/SW-24-3

## Features

<b>Current Meter</b>	Digital True RMS Current Meter
<b>Installed in Rack</b>	Vertical
<b>Remote Power Monitor</b>	Web, SNMP, Free Bundle Software
<b>Temp./Humidity</b>	Option Accessory
<b>Audible Alarm</b>	2 Phase, Warning and Overload
<b>Event Alert</b>	Email, Trap, Audible Alarm
<b>Protection</b>	Circuit Breaker
<b>Includes</b>	Mounting Bracket

## Specification

<b>General</b>	
Output	(21) IEC 320 C13 (3) IEC 320 C19
Input	(1) L6-30P attached power cord, 3 meters long
Protection	(3) 16 AMP Circuit Breaker
<b>Communication</b>	
IP Address	(1) Yellow LED
PDU Status	(1) Green LED
Power Status	(24) Red LED
Power Monitor	(1) RJ45 for Ethernet
Temp./Humidity Monitor	(1) RJ11
Current	3 Digits Meter Range: 0A ~ 20A Resolution: 0.1A Precision: $\pm 2\% \pm 0.1\text{AMP}$
<b>Operation</b>	
Input Voltage	208 V
Output Range	208 V
Frequency	50/60HZ full range
Max. Output Current	30 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	38 x 1783 x 56 mm
Weight	6.5 kg