


Pure Sine Wave Inverter SK Series

Model : SK2000-XXX



Features and Specifications

- ▣ Pure sine wave output (THD < 3%).
- ▣ Output frequency : 50/60Hz switch selectable
- ▣ Input & output fully isolation design
- ▣ High efficiency 89~95%
- ▣ "Low power saving mode" to conserve energy.
- ▣ Tri-Color indicators display input voltage, output load level and failure status.
- ▣ Loading controlled cooling fan
- ▣ Advanced microprocessor
- ▣ SC / OV / UV / OT / OL protections.



Specification	Model No.					
	SK2000-112	SK2000-124	SK2000-148	SK2000-212	SK2000-224	SK2000-248
Continuous Output Power	2000W					
Maximum Output Power (3Min.)	2300W					
Surge Rating	4000W					
Input voltage	12V	24V	48V	12V	24V	48V
Output Voltage	100 / 110 / 120V +/- 3%			220 / 230 / 240V +/- 3%		
Frequency (Switch Selectable)	50 / 60Hz +/- 0.05%					
Output Waveform	Pure Sine Wave (THD < 3%)					
Efficiency (full load)	89.0%	92.0%	93.0%	91.0%	94.0%	95.0%
No Load Current Draw	2.8A	1.5A	0.7A	2.64A	1.32A	0.65A
Stand-By Current Draw	0.60A	0.30A	0.15A	0.60A	0.25A	0.15A
Input Voltage Regulation	10.5-15 VDC	21.0-30 VDC	42-60 VDC	10.5-15 VDC	21.0-30 VDC	42-60 VDC
Input Level Indicator	Red / Orange / Green LED					
Load Level Indicator						
Failure Indicator						
Protection	Overload, Short Circuit, Reverse Polarity (Fuse), Over / Under Input Voltage, Over Temperature.					
Remote Control Unit	CR-6 / CR-7 / CR-8 Optional					
Safety Certification	Meet UL458			EN60950-1		
EMC	FCC Class A			EN55022: 1997	EN55024: 1997	e-mark e-13-022846
				EN61000-3-2: 1998	EN61000-3-3: 1995	
Operating Temperature Range	0 - 40 °C					
Storage Temperature Range	-30°C to 70°C					
Cooling	Loading controlled cooling fan (65°C ON , 45°C OFF)					
Dimensions	422(L)x208(W)x166(H)mm / 16.6(L)x8.18(W)x6.53(H) Inch					
Weight	9 kg / 19.8 Lbs.					

★ Note: The specifications are subject to change without notice