


Pure Sine Wave Inverter SK Series

Model : SK3000-XXX



Features and Specifications

- ▣ Pure sine wave output (THD < 3%).
- ▣ Output frequency : 50/60Hz switch selectable
- ▣ Input & output fully isolation design
- ▣ High efficiency 88~94%
- ▣ "Low power saving mode" to conserve energy.
- ▣ Tri-Color indicators display input voltage, output load level and failure status.
- ▣ Loading controlled cooling fan
- ▣ Advanced microprocessor
- ▣ SC / OV / UV / OT / OL protections.



Specification	Model No.					
	SK3000-112	SK3000-124	SK3000-148	SK3000-212	SK3000-224	SK3000-248
Item						
Continuous Output Power	3000W					
Maximum Output Power (3Min.)	3450W					
Surge Rating	6000W					
Input voltage	12V	24V	48V	12V	24V	48V
Output Voltage	100 / 110 / 120V +/- 3%			220 / 230 / 240V +/- 3%		
Frequency (Switch Selectable)	50 / 60Hz +/- 0.05%					
Output Waveform	Pure Sine Wave (THD < 3%)					
Efficiency (full load)	88.0%	91.0%	92.0%	90.0%	93.0%	94.0%
No Load Current Draw	2.0A	1.6A	0.8A	2.8A	1.5A	0.7A
Stand-By Current Draw	0.55A	0.35A	0.19A	0.55A	0.35A	0.19A
Input Voltage Regulation	10.5-15 VDC	21.0-30 VDC	42-60 VDC	10.5-15 VDC	21.0-30 VDC	42-60 VDC
Input Level Indicator	Red / Orange / Green LED					
Load Level Indicator						
Failure Indicator						
Protection	Overload, Short Circuit, Reverse Polarity (Fuse), Over / Under Input Voltage, Over Temperature.					
Remote Control Unit	CR-6 / CR-7 / CR-8 Optional					
Safety Cert.	Meet UL458			EN60950-1		
EMC	FCC Class A			EN55022: 1997 EN55024: 1997 EN61000-3-2: 1998 EN61000-3-3: 1995		e-mark e-13-022845
Operating Temperature Range	0 - 40 °C					
Storage Temperature Range	-30°C to 70°C					
Cooling	Loading controlled cooling fan					
Dimensions	452(L)x208(W)x166(H)mm / 17.80(L)x8.18(W)x6.53(H) Inch					
Weight	9.8 kg / 22 Lbs.					

★ Note: The specifications are subject to change without notice